



SMA Inverter Wi-Fi Reconnection Procedure



https://www.youtube.com/watch?v=npPB0_Z3HD0



REQUIREMENTS BEFORE INITIATING SEQUENCE:

- Physical access to your SMA Inverter
- Wi-Fi enabled device such as smartphone, tablet or computer
- Patience the average reconnection time is 10 minutes

	3	1
		• L net "SMA ser devi
ASUS Ilikettottaa SMA19920 Iseasel	00460	94
	inat.	13
		1

Look for a Wi-Fi twork in a form of A" followed by the rial number of the ice you are trying to connect to

> To connect to your inverter's Wi-Fi network you need to put in the "WPA2-PSK" password which is unique to your inverter

STEP

2

Security.



Page 1 of 2



SMA Inverter Wi-Fi Reconnection Procedure



https://www.youtube.com/watch?v=npPB0_Z3HD0



192,168,12,3 http://192,168,12,3/ is not available 192,168,12,3 19 SMA device 197,168,12,3//camartView SMA device 192,168,12,3//0/	0 K K K
http://192.168.12.3/ is not available 192.168.12.3 19 SMA device 192.168.12.3/CommitView SMA device 192.168.12.3/0/	R R R
19 SMA device 197,168 12 3/RomatView SMA device 197,168 12 3/R/	K K
SMA device 197,168,12.3/RomatView SMA device 192,168,12.3/R/	ĸ
SMA device 102.168.12.3/#/	7
103.100.12.2740	
	9 0
	98
Once connected, go	to
any browser on you	r
phone and type	
"192.168.12.3" in t	he

Login as "User" and for first time login you need to create a unique but easy to remember password

12

SMA

10.0

line.

192,168.12.3/1/

SUNNY BOY 5.0

Largier.

Longuage.

Experi-

Miel grad

1000

Permanent

STEP

4

Farget Lason and F

